

# GALVANIZED

**THICKNESS (min – max)**  
0.0120 in. – 0.1280 in.  
0.3048 mm – 3.2512 mm

**WIDTH (min – max)**  
35.5 in. – 73 in.  
901.7 mm – 1854.2 mm

## Ultra Low Carbon, Interstitial-Free (IF) Steel

- ASTM A653 Latest Edition
- SAE J2340
- DDS
- 180 Type A, B
- EDDS
- 210 Type A, B

## Low Carbon / Drawing Qualities

- ASTM A653
- SAE J1392
- CS Type A, B, C
- 035-045 (A, B, C, S, X, Y, Z)
- DS Type A, B
- DC01

## High Strength Low Alloyed (HSLA)

- ASTM A653
- SAE J2340 CR
- HSLAS Grade 40
- HSLAS Grade 300 X, Y
- HSLAS Grade 50
- HSLAS Grade 340 X, Y
- HSLAS Grade 55 Class 1, 2
- HSLAS Grade 380 X, Y
- HSLAS Grade 60
- HSLAS Grade 420 X, Y
- HSLAS Grade 70
- HSLAS Grade 490 X, F\*
- HSLAS Grade 80
- HSLAS Grade 550 X, F

## Structural Steels

- A653
- SAE J403
- SS Grade 33
- SAE No 1017
- SS Grade 37
- SAE No 1018
- SS Grade 40
- SAE No 1019
- SS Grade 50 Class 1, 2, 3 or 4
- SAE No 1020
- SS Grade 55
- SAE No 1021
- SS Grade 60
- SAE No 1022
- SS Grade 70\*
- SAE No 1023
- SS Grade 80 Class 1, 2 or 3

## Dual Phase Steel

- VDA Dual Phase
- CR330Y590T DP\*
- CR440Y780T DP\*
- CR590Y980T DP\*

\* Grade in development. Please inquire.

Grades shown are representative of the capabilities of Big River Steel's equipment. Actual grade and size capability of each material may vary in actual production. Cross-section properties may impact max and min capabilities. Please send inquiries to [salesinfo@bigriversteel.com](mailto:salesinfo@bigriversteel.com).