

COLD ROLLED

THICKNESS (min – max)

0.0120 in. – 0.1000 in.

0.3048 mm – 2.5400 mm

WIDTH (min – max)

36 in. – 72 in.

914.4 mm – 1828.8 mm

Please inquire for capabilities outside of stated ranges.

Ultra Low Carbon, Interstitial-Free (IF) Steel

- ASTM A1008 Latest Edition
- DDS
- EDDS
- SAE J2340
- 180 Type A, B
- 210 Type A, B

Low Carbon / Drawing Qualities

- ASTM A1008
- CS Type A, B, C
- DS Type A, B
- SAE J1392
- 035-045 (A, B, C, S, X, Y, Z)

High Strength Low Alloyed (HSLA)

- ASTM A1008
- HSLAS Grade 45 Class 1, 2
- HSLAS Grade 50 Class 1, 2
- HSLAS Grade 55 Class 1, 2
- HSLAS Grade 60 Class 1, 2
- SAE J2340 CR
- HSLAS Grade 300 X, Y
- HSLAS Grade 340 X, Y
- HSLAS Grade 380 X, Y
- HSLAS Grade 420 X, Y
- HSLAS Grade 490 X, F*
- HSLAS Grade 550 X, F

Structural Steels

- A1008
- SS Grade 25
- SS Grade 30
- SS Grade 33 Type 1, 2
- SS Grade 40 Type 1, 2
- SS Grade 45
- SS Grade 50
- SS Grade 60*
- SAE J403
- SAE No 1017
- SAE No 1018
- SAE No 1019
- SAE No 1020
- SAE No 1021
- SAE No 1022
- SAE No 1023

Cor-Ten A and B

- ASTM
- A242 Latest Edition*
- A606 Type 4 Latest Edition*

High Carbon

- SAE 1030*
- SAE 1035*
- SAE 1040*
- SAE 1050*
- SAE 1055*
- SAE 1065*
- SAE 1074*

Dual Phase Steel

- DP590*
- DP600*
- DP780*
- DP800*
- VDA Dual Phase
- CR330Y590T DP*
- CR440Y780T DP*
- CR590Y980T DP*
- SAE
- CR600DL1 DP*
- CR800DL DP*
- CR1000 DP*

Specialty Grades

- VDA TRIP
- CR400Y690T - TR*
- CR450Y780T - TR*

* Grade in development. Please inquire.

Grades shown are representative of the capabilities of Big River Steel's equipment. Actual grade and size capability of each material may vary in actual production. Cross-section properties may impact max and min capabilities.

Please send inquiries to salesinfo@bigriversteel.com.